Artemide

PRODUCT DATA SHEET

Hila

Composed by lamp and ground support pole.
Lamp unit is die-cast EN-AB 47100 aluminium.
UV resistant diffuser in shock resistant polycarbonate with satiny finish.
Support pole h=350cm above ground +50cm underground in extruded EN-AW 6060 aluminium, chromate treated and painted.

Light Grey Ral9002

LED Palo

650° **IP**65

W	Dimensions	Luminous Flux (lm)	Color	Code
24W	16x37 cm	1311lm		T085900



Hila LED	LED	luminaire
Power	24W	24W
Flux	1200lm	1311lm
CCT	4000K	4000K
CRI	75 typ	
Color Tolerance		
Service Life		
Efficiency		
Efficacy		

LED Floor

650° **IP**65

W	Dimensions	Luminous Flux (lm)	Color	Code
12W	16x37 cm	786lm		T085700



Hila LED	LED	luminaire
Power	12W	12W
Flux	786lm	786lm
CCT	4000K	4000K
CRI	75 typ.	
Color Tolerance		
Service Life		
Efficiency		
Efficacy		

LED Wall

650° **IP**65

W	Dimensions	Luminous Flux (lm)	Color	Code
24W	16x37 cm	1311lm		T085800



Hila LED	LED	luminaire
Power	24W	24W
Flux	1200lm	1311lm
CCT	4000K	4000K
CRI	75 typ	
Color Tolerance		
Service Life		
Efficiency		
Efficacy		

Designers

Carlo Colombo